

ViewGuard

DIGITAL SURVEILLANCE CAMERA

-1-


XC-CAM-XD6-015 Vandal & Weather Resistance Dome Camera

- color 1/3" Sharp CCD, 3.6mm board lens
- 380 TVL, 0.1 lux/F=2.0
- AGC, AWB, AES
- Dimension: 110(Ø) x 76(H) mm



XC-CAM-XD6-0AU UFO-in-ceiling type Dome Camera

- color 1/3" Sharp CCD, 3.6mm board lens
- 380 TVL, 0.1 lux/F=2.0
- AGC, AWB, AES
- Dimension: 98(Ø) x 53(H) mm



XC-CAM-XH6-011 PIR type hidden CCD Camera

- color 1/3" Sharp CCD, pinhole lens
- 380 TVL, 0.1 lux/F=2.0
- AGC, AWB, AES
- Dimension: 70(W) x 120(H) x 48(L) mm



XC-CAM-XO6-011 Smoke detector type hidden CCD Camera

- color 1/3" Sharp CCD, pinhole lens
- 380 TVL, 0.1 lux/F=2.0
- AGC, AWB, AES
- Dimension: 130(Ø) x 58(H) mm



XC-CAM-XB6-A8R Weatherproof IR Camera

- color 1/3" Sharp CCD, 36-IR LED
- 380 TVL, 0 lux / IR
- AGC, AWB, AES
- Dimension: 82(D) x 110 (L) mm



XC-CAM-CCD-29R Day & Night DSP Color CCD Camera

- color 1/3" Sony HR super HAD CCD image sensor
- 470 TVL, 0.1 lux/F=1.2 & 0 lux/IR
- IR pass (850nm) optical filter
- s/n ratio > 48dB
- video drive & DC drive lenses control
- BLC, auto white balance, AGC
- AC 220V
- Dimension: 60(W) x 50(H) x 125(L) mm



XC-CAM-PTZ-001 Pan/Tilt/18X Speed Dome CCD Camera (indoor type)

- color 1/4" Sony EXview HAD CCD sensor
- 470 TVL, 0.7 lux & 0 lux/IR
- s/n ratio > 50dB
- built-in 18 x 12 zoom lens 4.1 ~ 73.8mm
- auto iris, auto focus

XC-CAM-PTZ-002 (outdoor type)

- pan 360° endless, tilt 0° ~ 90°
- speed --> pan: 0.5° ~ 300°/sec, tilt: 0.5° ~ 150°/sec
- BLC, auto white balance, AGC
- AC 220V
- Dimension: 133(D) x 222(H) mm (indoor type)
200(D) x 320(H) mm (outdoor type)



Indoor type



Outdoor type

ViewGuard

DIGITAL SURVEILLANCE CAMERA

-2-

XC-CAM-XD6-052

Dome Camera

- color 1/3" Sharp CCD, 3.6mm board lens
- 380 TVL, 0.1 lux/F=2.0
- AGC, AWB, AES
- Dimension 88mm (Ø) X 63mm (H)



XC-CAM-XD6-A9R

IR Dome Camera

- color 1/3" Sharp CCD, 3.6mm board lens
- 380 TVL, 0 lux with built-in 21 units IR-LED
- IR projection distance 15 M
- AGC, AWB, AES
- Dimension 94mm (Ø) X 66mm (H)



XC-CAM-XPL-6AZ

PIR Camera w/. Floodlight

- color 1/3" Sharp CCD, 3.6mm board lens
- 380 TVL, 0.1 lux/F=2.0
- AGC, AWB, AES
- 140° PIR motion sensor
- AC 100 - 240V / 150W halogen lighting load capacity
- Time adjustable (by VR) : 4" ~ 12'
- Lux adjustable (by VR) : day ~ night
- Detection Range adjustable (by VR) : 5 M ~ 12 M
- Operating temperature -20° C ~ 40° C

