

PR 70C

Standalone or PC linked access control with Proximity reader.

- Card capacity 5.400 users.
- Can save 4.000 open door history record.
- Reading range from 14 - 20 cm (under normal environment).
- Operating mode** : Card + PIN, Card only, Facility code only, Keypad only, Opening and Inhibit.
- Built-in Clock and calendar.
- Built-in RS 232 / RS 485 interface
- Intranet network with TCP / IP converter (optional).
- Dimension (L x W x H) : 17.5 x 10.3 x 3.6 cm



PR 90C

Proximity Card reader with complete feature.

- Card capacity 10.000 users and save 10.000 open door history record.
- Reading range from 14 - 20 cm. (under normal environment)
- Built in clock and calendar.
- Built in RS 232 / RS 485 interface
- With real time printing function (RS 232 port), can be connected to a serial printer.
- Operating mode** : Card only, Card + PIN, Card or Keypad, Facility Code only, Opening, and Inhibit.
- Inside door can be installed a push button or PR 200 / PR 300 for indoor & outdoor access control.
- Anti intimidation function.
- Data is protected even after power failure.
- Dimension (L x W x H) : 16 x 18.5 x 4.8 cm



MR 90C / BR 90C

Magnetic/Barcode Reader for Time Attendance & Access Control.

- Using ISO ABA track II (for MR 90C)
- Using Code 39 Barcode (for BR 90C)
- Buffer memory up to 10.000 records.
- Built-in clock and calendar.
- Built-in RS 232 / RS 485 interface.
- Intranet network with TCP / IP converter (optional).
- Dimension (L x W x H) : 16 x 18.5 x 4.8 cm.



PR 80C

Standalone or PC linked access control with Proximity reader.

- Support 10.000 users.
- Reading range from 10 - 16cm (under normal environment).
- Can save 10.000 door open history record.
- With 60 holiday setting fuction
- With real time printing function (RS 232 port), can be connected to a serial printer.
- Operating mode** : Card only, Card + PIN, Card or Keypad, Facility Code only, Opening, and Inhibit.
- Inside door can be installed a push button or PR 200 / PR 300 for indoor & outdoor access control.
- Built-in clock and calendar.
- Built-in RS 232 / RS 485 interface.
- Intranet network with TCP / IP Converter (option).
- Dimension (L x W x H) : 14.7 x 11.9 x 4.0 cm.

